



REFRIGERATORS AND FREEZERS



Model	Doors	Capacity (cu.ft)
CR1	1	23
CR2	2	49
CR3	3	72
CF1	1	23
CF2	2	49
CF3	3	72

STANDARD FEATURES

- Solid state thermostat with digital display
- Stainless steel front and sides
- Field reversible 1-door units
- 3 heavy duty baked epoxy racks
- Self closing doors remain open past 90°
- Non twist solid mullions on 2 & 3 door units
- Environmentally friendly HFC 134A and 404A
- EZ slide out condenser
- Full length integrated door handle
- Whisper quiet
- Solid construction
- Holds sheet pans front to back
- High efficiency polyurethane insulation
- Zero clearance back and sides

REFRIGERATION

Items	Description	Items	Description
Front, top & sides	Stainless steel	Temperature control	Solid state thermostat/Digital display
Doors	Stainless steel / ABS liner	Approvals	UL-EPH
External back	Aluminum	Refrigerating system	Capillary tube
Cabinet interior	Powder coated aluminum	Refrigerant	(CR) R134a; (CF) R404a
Interior floor	Stainless steel	Temperature range	(CR) 34-38F; (CF) -4-0F
Insulation	Polyurethane (CFC free)	Evaporator	Powder coated aluminum/copper
Shelves	Heavy duty, PVC coating	Condensing unit	Bottom mounted



DETAILS AND DIMENSIONS

Model	Doors	Capacity (cu.ft)	Shelves	Cabinet Dim (inches)			HP	Voltage	Amps	NEMA Plug	Cord Length	Crated Weight
				L	D	H						
CR1	1	23	3	27	33.7	82.7	3/8	115/60/1	6	5-15P	10	350
CR2	2	49	6	54	33.7	82.7	1/2	115/60/1	9	5-15P	10	518
CR3	3	72	9	81	33.7	82.7	5/8	115/60/1	10	5-15P	10	669
CF1	1	23	3	27	33.7	82.7	5/8	115/60/1	9	5-15P	10	364
CF2	2	49	6	54	33.7	82.7	1	115/60/1	12	5-15P	10	568
CF3	3	72	9	81	33.7	82.7	1-1/4	115/60/1	17	5-20P	10	776

