Item #



Standard Features

- Powerful 1/2 HP custom built motor
- Three fixed speeds
- Gear driven, high torque transmission
- Heat-treated hardened steel alloy gears and shafts
- Permanently lubricated transmission
- Thermal overload protection
- Rigid cast iron body
- Stainless steel bowl guard with built in ingredient chute
- NSF approved enamel gray paint
- Front mounted controls
- 15 minute timer
- Industry standard #12 attachment hub
- Safety interlocked bowl guard and bowl lift
- Non-slip rubber feet
- 6 foot cord and ground plug

NSF.





Globe

SP20 20 Quart Mixer

Model SP20 - 20 Quart Mixer

Built into each mixer is the quality of workmanship and design synonymous with Globe.

Standard Accessories

- 20 quart stainless steel bowl
- Flat beater (aluminum)
- Stainless steel wire whip
- Spiral dough hook (aluminum)

Optional Attachments/Accessories

- □ Slicer/shredder/grater for #12 hub
- □ Meat grinder for #12 hub
- 10 quart adapter kit
- Pastry knife
- □ Flat beater (stainless steel)
- Spiral dough hook (stainless steel)
- Mixer table with undershelf

Standard Warranty

• 2 years parts and one year labor

Approved By:_____

Date:

GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd. Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147

SP20

el)

20 Quart Mixer

Clobe Ope



20 Quart Mixer

Motor: 1/2 HP, grease packed ball bearing, air cooled, 115/60/1, 10 amps. Thermal overload protection (automatic reset).

Finish: NSF approved enamel gray paint.

Capacity: 20 quart (19 liter) bowl.

Transmission: Fixed speed transmission is made of heat treated. hardened alloy, precision milled gears that operate the planetary action and provide high torque mixing power. The gears are packed in a long lasting grease, and all shafts are mounted in ball bearings.

Safety Interlocks: The bowl guard and bowl lift lever are interlocked. The mixer will automatically shut down when the guard is opened or the bowl is lowered.

Agitator Speeds (RPMs):

Low	104
Intermediate	194
High	353

Attachment Speeds (RPMs):

Low	59
Intermediate	110
High	201

Specifications

Standard Equipment: Standard equipment includes a 20 quart #304 series stainless steel bowl, aluminum spiral dough hook, stainless steel wire whip, aluminum flat beater, stainless steel bowl guard with built in ingredient chute, 15 minute timer, and #12 attachment hub. A sturdy hand lever on the body column raises and lowers the bowl as well as locking in place at the top and bottom positions.

Cord: 6 ft. flexible three wire cord and around plug.

Dimensions:

Foot Print = 18.7" x 16.7" (47.5cm x 42.4cm) Overall Length = 21.9" (55.6cm) Overall Width = 22.4" (56.9cm) Overall Height = 34.5" (87.6cm)

Shipping Information:

Freight Class: 85 Net Weight: 176 lbs. (80 kgs.) Shipping Weight: 270 lbs.(122.5kgs.) Shipping Dimensions: 32"W x 40"D x 48"H (81.3cm x 101.6cm x 121.9cm) Cartons are affixed to a skid (pallet). The weight and dimensions of this skid are included above and may vary from shipment to shipment.

Optional Accessories:

XXACC10-20 Adapter Kit (includes a 10 quart bowl, wire whip, dough hook, flat beater, and bowl adapter to adapt 20 quart mixer to a 10 quart capacity)

XXPASTRY-20	Pastry Knife
XXBEAT-20SS	Stainless Steel Flat
	Beater
XXHOOK-20SS	Stainless Steel
	Spiral Dough Hook

XTABLE Mixer Table with Undershelf (stainless steel top with galvanized steel undershelf and legs) 30"W x 24"D x 24"H (76.2cm x 61cm x 61cm)

Optional Attachments:

XMCA-SS Meat Grinder Assembly (Polished stainless steel cylinder, worm, ring, and pan. Includes knife, 3/16" plate, stainless steel pan, and pusher.)

Chopper Plate Sizes Available:

CP02-12	1/16"	(2mm)
CP04-12	5/32"	(4mm)
CP05-12	3/16"	(5mm)
CP06-12	1/4"	(6mm)
CP08-12	5/16"	(8mm)
CP10-12	3/8"	(10mm)
CP12-12	1/2"	(12mm)
CP14-12	9/16"	(14mm)
CP16-12	5/8"	(16mm)
CP18-12	11/16"	(18mm)
CP00-12	Stuffing	Plate
XST12 1/2"	stuffing	tube (sheep)
XST34 3/4"	stuffing	tube (hog)

XVSGH 9" Slicer/Shredder/Grater Housing Only (no plates included-must select from plates below)


XASP Adjustable slicing plate **XPH** Plate holder - *only 1 required

Shredding/Grating Plates:

XSP332*	3/32"	(2.3mm)
XSP316*	3/16"	(4.7mm)
XSP14*	1/4"	(6.3mm)
XSP516*	5/16"	(7.9mm)
XSP12*	1/2"	(12.7mm)
XGP*	Grating plate	

2153 Dryden Rd. Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147

GLOBE FOOD EQUIPMENT COMPANY



precisely.

www.qlobeslicers.com

Specifications are subject to change without notice.