

Continental

Refrigerator

WORKTOP BACKSPLASH REFRIGERATORS



Models Available

- SW27-BS
- SW32-BS
- SW36-BS
- SW60-BS
- SW48-BS
- SW72-BS

Utilizing Environmentally Safe,
CFC-free R-134a Refrigerant

Standard Features

- Modern, State-of-the-Art Styling
- Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- Easily Serviceable Back Mounted Compressor
- 2" Non-CFC Polyurethane Foam Insulation
- Spring Loaded, Self Closing Door
- Magnetic Snap-In Gasket
- 5" Casters, two with brakes; two without brakes
- Heavy-Duty, Epoxy-Coated Steel Shelves
- Interior Hanging Thermometer
- Unique Air Flow Distribution Keeps Product at Uniformly Constant Temperatures
- Cabinet Construction Consisting of Stainless Steel Front and Top, Aluminum End Panels, Case Back and Interior
- Non-Corrosive, Plasticized Fin Evaporator Coil
- Completely Enclosed, Vented and Removable Case Back
- Automatic, Energy Saving, Non-Electric Condensate Disposal
- 10' Cord and Plug Attached

Optional Features & Accessories

- Legs
- Remote Models R
- Stainless Steel End Panels -SA Models
- Stainless Steel Interior & Exterior-SS Models
- Stainless Steel Finished Back in Lieu of Aluminum
- Electric Condensate
- Additional Shelves
- Glass Door-GD
- Door Locks
- Single Overshelf
- Double Overshelf
- Stainless Steel Roll Out Drawers in Lieu of Door-D



c



WORKTOP BACKSPASH REFRIGERATORS

SPECIFICATIONS

	SW27-BS	SW32-BS	SW36-BS	SW48-BS	SW60-BS	SW72-BS
DIMENSIONAL DATA						
Net Capacity (cu. ft.)	7.4	9.0	10.3	13.4	17.0	20.6
Width, Overall (in.)	27½	32	36	48	60	72
Depth, Overall (incl. Hdls.) (in.)	30	30	30	30	30	30
Depth, Body Only (Less Door(s))(in.)	27½	27½	27½	27½	27½	27½
Height (incl. 5" Casters) (in.)	41	41	41	41	41	41
Shelf Area (sq. ft.)	3.5	3.9	4.6	6.8	8.1	10.2
No. of Shelves	1	1	2	2	2	3
No. of Doors	1	1	2	2	2	3
Interior Depth (in.)	20	20	20	20	20	20
Interior Height (in.)	26¼	26¼	26¼	26¼	26¼	26¼
Interior Width (in.)	24½	28	32	44	56	68
Condensing Unit Size (H.P.)	⅕	⅕	⅕	⅕	¼	¼
Cabinet Electrical	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Amps	6.1	6.3	6.3	7.1	7.6	8.6
Fans	2	2	2	3	3	4
Shipping Weight (lbs.)	165	180	220	248	284	318
Shipping Height (in.)	43¼	43¼	43¼	43¼	43¼	43¼
Shipping Length (in.)	35¾	39	43	55	68¼	80¼
Shipping Depth (in.)	37¼	37¼	37¼	37¼	37¼	37¼

