

Project _____
 Item _____
 Quantity _____
 CSI Section 11400
 Approval _____
 Date _____

Conserver® XL-E

Models

Conserver® XL-E



Standard Features

- Electronic timer
- Internal sump design
- Built-in waste accumulator
- Delimer switch for easy removal of hard water deposits
- Removable scrap screen
- Air gap instead of vacuum breaker
- Door switch
- Convenient top mounted controls
- Auto start
- Interchangeable upper and lower stainless steel wash/rinse arms
- Wash thermometer
- Low chemical indicator lights
- Stainless steel adjustable bullet feet

Mandatory Specs

Specify voltage _____

Options

- Water Hammer Arrestor
- Scaltrol
- False Panel
- Flanged Feet
- Audible Low Product Alarm
(available only on 115v models)

Accessories

- 36-Compartment Rack
 - 4-1/8" tall (105 mm)
 - 5-5/8" tall (143 mm)
 - 7" tall (178 mm)
- Combination Rack
- Peg Rack

Specifications

Uses 1.02 gallons (3.9 liters) water per rack

39 racks per hour (Normal cycle)

Single point electrical connection

Self-draining stainless steel pump eliminates soil/detergent carryover between wash and rinse cycles

Fill and Dump design disposes of dirty water, replacing it with a fresh water rinse every cycle

Field convertible from straight to corner and corner to straight for flexible installations and applications

17-1/4" (438 mm) vertical inside clearance

Built-in chemical pumps and priming switches

Large removable scrap screen

Durable stainless steel construction



Intertek



Intertek



LEGEND
 A - Electrical Connection (1 1/8" Hole)
 B - Water Inlet (3/4" NPT)
 C - Drain Connection (2" NPT)
 D - Chemical Connection (7/8" Hole)

All dimensions from the floor can be increased 1 1/2" using the machine's adjustable feet.

MODEL NO.	MACHINE DIMENSIONS				DRAIN HEIGHT	SHIPPING INFORMATION					
	HEIGHT	WIDTH	WIDTH BETWEEN DISHTABLES	DEPTH		WEIGHT	CLASS	CUBE	HEIGHT	WIDTH	DEPTH
Conservar® XL-E	68-1/2" (1740 mm)	30-3/8" (773 mm)	25-1/4" (641 mm)	29-1/2" (750 mm)	8-7/8" (224 mm)	230 lbs (105 kg)	300	58.15 cu. ft.	72-1/2" (1842 mm)	33" (838 mm)	42" (1067 mm)

DIMENSIONS		WATER	
Wall Clearance (minimum)	4" (102 mm)	Inlet Temperature	120 °F min. (49 °C); 140 °F (60 °C) recommended
Standard Table Height	34" (864 mm)	Gallons per Hour	39.78 gal (150.6 L)
Inside Clearance	17-1/4" (438 mm)	Gallons per Rack	1.02 gal (3.9 L)
Machine Height with Door Open	78" (1981 mm)	Waterline Size IPS (minimum)	3/4"
		Drainline Size IPS (minimum)	2"
		Flow Pressure (PSI)	20 ± 5
		Wash Tank Capacity	1.02 gal (3.9 L)
		Minimum Chlorine Required (PPM)	50

OPERATING CAPACITY		ELECTRICAL	
Racks per Hour	39	Power Supply	Total Amp Load
Dishes per Hour	975	115/60/1	10.0 A
Glasses per Hour	1,404	208/60/1	5.0 A

OPERATING CYCLE (seconds)					WASH PUMP MOTOR	
Wash	Rinse	Dwell	Total Cycle	Wash Pump	1 HP	
42	25	20	87			

OPERATING TEMPERATURES	
Wash	120 °F min. (49 °C); 140 °F (60 °C) recommended
Rinse	120 °F min. (49 °C); 140 °F (60 °C) recommended

HOW TO SPECIFY: Conservar® XL-E

Jackson WWS, Inc.
 Shipping Address: 6209 North U.S. Highway 25E, Gray, KY 40734
 Mailing Address: P.O.Box 1060, Barbourville, KY 40906
 Telephone: 888-800-5672 • Fax: 606-523-1799
 Email: info@jacksonwws.com
 07610-004-00-91 [05/15/2020]

www.jacksonwws.com