OD Series, Remote & Self-Contained Open Dairy Merchandisers





OD Series, Remote & Self-Contained Open Dairy Merchandisers

"While Everyone Else Says There Optional ...

... only Marc offers these kind of features STANDARD!

- · Decorator colored sides of your choice from Marc's enormous
- Night Shades lock in your refrigeration overnight.
- Four levels of mirror stainless steel shelving or Romate rusels

 THREE LEVELS OF MIRROR STANDESS STANDARD CONTRACTOR STANDARD. Freon 22 valve installed on remote and self-contained models. Prodel
- · Dial thermometer for accurate temperature readings.
- · Enhanced product lighting from top canopy and under two levels of mirror stainless steel shelving.
- Optional 5 levels of product lighting.
- . Drain is 1" pipe thread for easy cleaning (drain connection required in field, remote and self-contained models).

- Front bumper made of high density PVC for shopping cart
- · Side panels have 1/4" plexiglass for maximum visibility and
- · Insulation is full density, solid core urethane.
- · Automatic time clocks are standard for self-contained and remote.
- · Mirror finish stainless steel trim, caps, moulding, main deck and shelves.

NOTE: Designed for use in locations with air conditioning, where temperature and relative humidity DO NOT exceed 75°F and 55% R.H. (Excessive condensation & loss of temperature may occur).

We reserve the right to change specifications without notice.

MODEL	LENGTH	HEIGHT	DEPTH	UNIT INSTALLED	UNIT RECOMMENDED (not included)	MINIMUM CIRCUIT AMPACITY ELECTRICAL DATA	APPROX. SHIPPING WEIGHT
OD-6R	72 1/2**	79½"	34½"	х	1½ H.P.*	115/1/60 8 amps	700 lbs
OD-8R	94½"	79½"	34½"	х	2 H.P.*	115/1/60 12.5 amps	800 lbs
OD-10R	116½**	79½''	341/2**	х	3 H.P.*	115/1/60 12.5 amps	1000 lbs
OD-12R	138½"	791/2**	34½''	х	3 H.P.*	115/1/60 14.5 amps	1140 lbs
OD-4S/C	49	791/2**	34½" plus 3" removable wall spacer for compressor air flow	1 H.P.	х	115/1/60 8 amps lights & fans	675 lbs
						230/208-60-1 9.5 amps unit & clock	
OD-6S/C	721/2**	791/2**	34½" plus 3" removable wall spacer for compressor air flow	1½ H.P.	X	115/1/60 8 amps lights & fans	775 lbs
						230/208-60-1 15.5 amps unit & clock	

^{*}This size condenser unit is RECOMMENDED for this model. Consult a competent refrigeration mechanic to determine the appropriate size for your specific application. The appropriate condenser will vary depending on length of run, indoor/outdoor use, etc. Do not install near heat, A/C Air ducts, A/C thermostats or doorways.









